


FREQUENCY (GHz): DC - 2.0
 VSWR (MAX): 1.2:1
 INSERTION LOSS (dB, MAX): 0.10
 POWER:
 AVG (W): 10
 PEAK (W): 50
 IMPEDANCE: 50 Ohms
 TORQUE: 5 IN-OZ
 MATERIAL: STAINLESS STEEL, COPPER ALLOY
 FINISH: PASSIVATE, IRRIDITE
 MARKING: LOT NUMBER

THIRD ANGLE PROJECTION



DIMENSIONS ARE IN INCHES.
 REMOVE ALL BURRS AND SHARP EDGES .005 MAX, UNLESS OTHERWISE SPECIFIED, SURF FINISH 63
 TOLERANCES ARE:
 FRACTIONS ±1/64 DECIMALS 2 PLACES ±.03 ANGLES ±1/2°
 3 PLACES ±.010

INTERPRET DIMENSIONS & TOLERANCES PER ASME Y14.5M

DIAMOND ANTENNA & MICROWAVE CORP
 LITTLETON, MA 01460

TITLE: SINGLE CH SMA ROTARY JOINT

SIZE: B CAGE CODE: 01882 DRAWING NUMBER: CAT 56-2124-0

SCALE 4:1 WEIGHT (EST.): SHEET 1 OF 1