



DESIGN SPECIFICATIONS

ELECTRICAL

FREQUENCY (GHz) :	5.850-6.725
VSWR (MAX) :	1.2:1 MAX
VSWR WOW (MAX) :	.05
INSERTION LOSS (MAX) :	.20 dB
INSERTION LOSS WOW (MAX) :	.05 dB
POWER, AVG :	3.5 KW

MECHANICAL & ENVIRONMENTAL

ROTATIONAL SPEED :	2.5 RPM MAX
TEMPERATURE, OPERATING :	-32° C TO +53° C
TEMPERATURE, STORAGE :	-60° C TO +75° C
HUMIDITY (OPERATING) :	UP TO 95% NON-CONDENSING
HUMIDITY, STORAGE:	UP TO 100% CONDENSING ALTITUDE
ALTITUDE, OPERATING:	UP TO 10,000 FT ABOVE MSL
ALTITUDE, STORAGE:	UP TO 40,000 FT ABOVE MSL
SOLAR LOADING:	1120 W/M ²
SEALED:	100% WATERPROOF REGARDLESS OF POSITION
LEAKAGE :	0.05 SCFH (24 CC/MIN) @ 1 PSIG
PRESSURE :	1 PSIG DRY AIR
TORQUE :	70 OZ-IN MAX
WEIGHT :	3.3 LBS TYP., 10 LBS MAX
MATERIAL :	ALUMINUM ALLOY PRIMARILY
FINISH :	TBD
	(MASK WHERE INDICATED BY Δ)

MARKING : DIAMOND STANDARD LABEL TO INCLUDE DIAMOND PART NO. & SER. NO.

ROHS COMPLIANT

THIRD ANGLE PROJECTION

DIMENSIONS ARE IN INCHES.
 REMOVE ALL BURRS AND SHARP EDGES .005 MAX, UNLESS OTHERWISE SPECIFIED. SURF FINISH 63
 TOLERANCES ARE:
 FRACTIONS DECIMALS ANGLES
 $\pm 1/64$ 2 PLACES $\pm .03$ $\pm 1/2$
 $\pm 1/64$ 3 PLACES $\pm .010$

INTERPRET DIMENSIONS & TOLERANCES PER ASME Y14.5M

DIAMOND ANTENNA & MICROWAVE CORP
LITTLETON, MA 01460

TITLE: SINGLE CH, I-STYLE WR137 R/J

SIZE: C	CAGE CODE: 01882	DRAWING NUMBER: CAT 33-645-0
---------	------------------	------------------------------

SCALE: 1:1	WEIGHT (EST.):	SHEET 1 OF 1
------------	----------------	--------------