



NOTE:

1. PERFORMANCE

FREQUENCY: 14.9-15.1 GHz
 VSWR: 2.0 : 1.0 MAX
 INSERTION LOSS: 1.30 dB MAX
 MAX POWER: 10 WATTS IN VACUUM
 OPERATING TEMPERATURE: -50 DEG C TO 70 DEG C.
 IMPEDANCE: 50 OHMS

THIRD ANGLE PROJECTION		
DIMENSIONS ARE IN INCHES. REMOVE ALL BURRS AND SHARP EDGES .005 MAX, UNLESS OTHERWISE SPECIFIED. SURF FINISH 63 TOLERANCES ARE: FRACTIONS DECIMALS ANGLES $\pm 1/64$ 2 PLACES $\pm .03$ $\pm 1/2^\circ$ $\pm 1/64$ 3 PLACES $\pm .010$		
INTERPRET DIMENSIONS & TOLERANCES PER ASME Y14.5M		

DIAMOND ANTENNA & MICROWAVE CORP LITTLETON, MA 01460		
TITLE: ROTARY JOINT-COAX CABLE ASSEMBLY		
SIZE: C	CAGE CODE: 01882	DRAWING NUMBER: CAT 57-2124-0
SCALE 1:1	WEIGHT (EST.):	SHEET 1 OF 1